

Carbon Filter Product Data Sheet

Automatic Water Filter Systems

3150 Series

Standard Features:

Fleck 3150 Lead-Free Brass Valve
2" Female Inlet/Outlet Connections (FNPT)
Motor-Driven Piston-Operated
Virgin Granular Activated Carbon (GAC)⁽¹⁾
Fiberglass Resin Tank
Fleck 12 Day Electro Mechanical Timer
Timer Controlled Backwashes



Product Specifications

Model	Maximum Service Flow Rates (gpm) ⁽¹⁾	Backwash Flow Rate (gpm)	Carbon (ft ³)	Tank Dimension (in)
AWS FC24 FRP 3150 TC	38	30	10	24 x 72
AWS FC30 FRP 3150 TC	56	50	15	30 x 72
AWS FC36 FRP 3150 TC	75	70	20	36 x 72

(1) - Two minute empty bed contact time for chlorine removal.

Operating Specifications

Water Temperature: Minimum 35°F Max 120°F
Pressure Range: Minimum 30 psi Max 120 psi
Electrical Requirements: 120 VAC Standard Outlet

Optional Features

ASME Code Vessels Duplex & Triplex
Skid Mounted Pressure Gauges
Catalytic Carbon Electronic Control

Deionizer Systems · Water Softeners · Filtration · Reverse Osmosis Systems · Automatic Strainers · UV Disinfection ·
Equipment Supply & Installation · Turnkey Systems · Upgrades & Retrofits · Maintenance & Repair ·
Specialized Technical Support · Portable Rental Systems · Custom Systems · Engineering Design Assistance



All Water Systems, Inc.
1475 Airbrake Avenue
Turtle Creek, PA 15145
412-824-6560 · 412-824-6573 (fax)
allwatersystems.com · sales@allwatersystems.com